Calculating ISO 26262 functional safety and reliability metrics to identify and address hotspots early in the design cycle and guide impactful design changes

Overview

Key Benefits

Key Features




Figure 1: Static analysis approach to calculate single point fault metric

Static Calculation of Error Propagation

ð	SoftErro	Sort by SPF	r taopt21)		
Ele View Help		Contr.	111 Jan 19		
Search . Based on color in 0.1.M	🔜 e e 🛪 🔳	Costgure columns Contg	are columns		
Instance Hierarchy	Module Name	SPFM Contribution	Lambda Reg	Contribution(%)	_
core_cascade	core_cascade	1.23763	11.760000	10.52	_
agu	agu_structural	0.619185		5.27	
= PCU = ALU	pcu_structural	0.452879 0.165417		2.85	
= bus switch	alu_struc bus_switch	0.00015435		0.00	
	Control of the second sec	0.00 0.00	Sattlena freesen	ovre, sessade anj tee langit211	-
		the year law			
		a N 🖉 Miller	5	New Street and Second Second	
		and the second			
		9 VAD (01)	*/DW03_rog = pl 0.1%	1.36	_
		- la result	TI FOCE ON	D 000000 0.00 D 000000 0.00	
		AC 1905 TO	TL FOCE D.M.	0.000000 0.00 0.00000 0.00 0.00000 0.00	
		-10 FR05	ITL FOCE D.01	D 080000 R 08	
		UR THEATT	10.0 3004 111	0.000000 0.00 0.000000 0.00	
		-'m reg #i	TL FOCE 0.01	0.000001 0.00	
		THE PARTY OF THE P	TT FOCE 0.01	0.000000 0.09. 0.0000000 0.08	
		in realized as	TTL FORE 0.01	1000000 0.00 0.00000 0.00	
		-W, M0014	(11 40CE 0.01 01 FDCE 0.01	0.000000 0.00	

Figure 2: SPFM Browser identifies the blocks in the design with the highest probability causing functional safety failure

Key Features

For more information about Synopsys products, support services or training, visit us on the web at www.synopsys.com, contact your local sales representative or call 650.584.5000

